

JAMAIL HARDWOODS

SUPPLIER · INSTALL · DESIGN

DATA SHEET

Jamail Arte

Designer Patterns 2025

Houston's B2B Hardwood Flooring Partner

2643 Colquitt St · Houston, TX 77098 · By Appointment

832-930-5936 · trade@jamailhardwoods.com · jamailhardwoods.com



Pearl **3.5"** **Select**
 Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm
Plywood thickness (mm)	12 mm
Length (ft)	21.25" (540 mm)
Width (in)	3.5" (90mm)

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select. Minimal knots.
 Maximum diameter of 10 mm and repaired with filler.
 Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



Crystal **3.5"** **Select**
 Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm
Plywood thickness (mm)	12 mm
Length (ft)	21.25" (540 mm)
Width (in)	3.5" (90mm)

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select. Minimal knots.
 Maximum diameter of 10 mm and repaired with filler.
 Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



Smoke Name **3.5"** Width **Select** Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm
Plywood thickness (mm)	12 mm
Length (ft)	21.25" (540 mm)
Width (in)	3.5" (90mm)

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select. Minimal knots. Maximum diameter of 10 mm and repaired with filler. Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



Earth Name **3.5"** Width **Select** Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm
Plywood thickness (mm)	12 mm
Length (ft)	21.25" (540 mm)
Width (in)	3.5" (90mm)

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select. Minimal knots.
 Maximun diameter of 10 mm and repaired with filler.
 Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

